



Catalog Number	
Project	Type

## Features & Specifications

### Construction

Made from a compression molded, fiberglass reinforced polyester composite housing. An Anti-Siphon Chamber is provided to ensure no water can enter the main housing. ETL listed for wet locations.

### Optical System

A variety of optical systems are available depending on the bullet size and wattage chosen. Up shields, down shields, and tube shields are all available. Contact the factory for additional options needed for specific applications.

### Electrical System

Available with a 50W Mercury Vapor multitap CWA ballast. Pre-wired at specified voltage using a quick disconnect. Two 3/4" NPT and two 1/2" NPT conduit entries are provided.


### Mounting

The Burial Box is designed for direct burial mounting with the appropriate backfill. See mounting instructions for specific information regarding installation.

### Finish

Color impregnated composite box features Dark Bronze finish as the standard.

## CBB SERIES 50W Mercury Vapor Bullet with Composite Burial Box



### DIMENSIONS

Est Shipping Weight: 12 lbs  
for burial box only.



Please contact your Techlight Sales Representative for more information.  
All dimensions subject to change without notice.

### Ordering Nomenclature

Ex: (50W Mercury Vapor, R30 Aluminum, Up Shield, OD Green, MV50R30CMED, 120V = CBB01-2-4-1-3-1)

<b>CBB01</b>					
--------------	--	--	--	--	--

SERIES	BULLET	SHIELD	FINISH	LAMP	VOLTAGE
CBB01	1 - R20 Aluminum	1 - R20 Down Aluminum	1 - OD Green	0 - None	1 - 120 Volt
50W Mercury Vapor	2 - R30 Aluminum	2 - R20 Up Aluminum	2 - White	1 - MV50R20MED	2 - 208 Volt
	3 - R30 Copper	3 - R30 Down Aluminum	3 - Bronze	2 - MV50R30MED	3 - 240 Volt
	4 - R20 Copper	4 - R30 Up Aluminum	4 - Black	3 - MV50R30CMED	4 - 277 Volt
		6 - R30 Up Copper	5 - Special		
		7 - R20 Down Copper	6 - Natural Copper		
		8 - R30 Down Copper			
		9 - R20 Up Copper			
		14 - R20 Up Cast Aluminum			
		15 - R30 Up Cast Aluminum			