

Catalog Number	
Project	Туре

Features & Specifications

Construction

Made from a compression molded, fiberglass reinforced polyester composite housing. An Anti-Siphon Chamber is provided to ensure no water can enter the main housing. ETL listed for wet locations.

Optical System

A variety of optical systems are available depending on the bullet size and wattage chosen. Up shields, down shields, and tube shields are all available. Contact the factory for additional options needed for specific applications.

Electrical System

Available with a 35W Metal Halide multitap CWA ballast. Prewired at specified voltage using a quick disconnect. Two $\frac{3}{4}$ " NPT and two $\frac{1}{2}$ " NPT conduit entries are provided.

Mounting

The Burial Box is designed for direct burial mounting with the appropriate backfill. See mounting instructions for specific information regarding installation.


Finish

Color impregnated composite box features Dark Bronze finish as the standard.

CBB SERIES 35W Metal Halide Bullet with Composite Burial Box



DIMENSIONS



Est Shipping Weight: 12 lbs for burial box only.





Please contact your Techlight Sales Representative for more information. All dimensions subject to change without notice.

Ordering Nomenclature

Ex: (35W Metal Halide, R30 Aluminum, Up Shield, OD Green, MH35PAR30FLMED, 120V 4 CBB04-2-2-1-1-1)

CBB04					
SERIES CBB04 35W Metal Halide	BULLET 1 - R20 Aluminum 2 - R30 Aluminum 4 - R20 Copper 5 - R30 Copper	SHIELD 1 - R30 Down Aluminum 2 - R30 Up Aluminum 4 - R30 Up Copper 5 - R20 Up Copper 6 - R20 Up Aluminum 7 - R20 Down Copper 8 - R30 Down Copper 9 - R20 Down Aluminum 10 - R30 Up Tube Aluminum 11 - R20 Up Cast Aluminum 12 - R30 Up Cast Aluminum	FINISH 1 - OD Green 2 - White 3 - Bronze 4 - Black 5 - Special 6 - Natural Copper	LAMP 0 - None 1 - MH35PAR30FLMED 2 - MH35PAR309SPMED 3 - CDM35WPAR20NFL 4 - CDM35PAR20SP	VOLTAGE 1 - 120 Volt 2 - 208 Volt 3 - 240 Volt 4 - 277 Volt