



Catalog Number	
Project	Type

Features & Specifications

Construction

Made from a compression molded, fiberglass reinforced polyester composite housing. An Anti-Siphon Chamber is provided to ensure no water can enter the main housing. ETL listed for wet locations.

Optical System

A variety of optical systems are available depending on the bullet size and wattage chosen. Up shields, down shields, and tube shields are all available. Contact the factory for additional options needed for specific applications.

Electrical System

Available with a 70W Metal Halide multitap CWA ballast. Pre-wired at specified voltage using a quick disconnect. Two 3/4" NPT and two 1/2" NPT conduit entries are provided.


Mounting

The Burial Box is designed for direct burial mounting with the appropriate backfill. See mounting instructions for specific information regarding installation.

Finish

Color impregnated composite box features Dark Bronze finish as the standard.

CBB SERIES 70W Metal Halide Bullet with Composite Burial Box



DIMENSIONS

Est Shipping Weight: 12 lbs
for burial box only.



Please contact your Techlight Sales Representative for more information.
All dimensions subject to change without notice.

Ordering Nomenclature

Ex: (70W Metal Halide, R40 Aluminum, Up Shield, OD Green, CMH70PAR38SP15, 120V = CBB05-2-4-1-4-1)

CBB05					
--------------	--	--	--	--	--

SERIES	BULLET	SHIELD	FINISH	LAMP	VOLTAGE
CBB05 70W Metal Halide	1 - R30 Aluminum 2 - R40 Aluminum 3 - R30 Copper 4 - R40 Copper	1 - R30 Down Aluminum 2 - R30 Up Aluminum 3 - R40 Down Aluminum 4 - R40 Up Aluminum 6 - R30 Up Copper 8 - R40 Up Copper 9 - R30 Down Copper 10 - R40 Down Copper 11 - R30 Up Tube Aluminum 12 - R30 Up Cast Aluminum 13 - R40 Up Cast Aluminum	1 - OD Green 2 - White 3 - Bronze 4 - Black 5 - Special 6 - Natural Copper	0 - None 1 - MH70PAR30FLMED 2 - MH70PAR30SPMED 4 - CMH70PAR38SP15 7 - MH70MED-FLREF 8 - MH70MED-SPREF 9 - CMH70PAR38/WFL	1 - 120 Volt 2 - 208 Volt 3 - 240 Volt 4 - 277 Volt