



Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

APPLICATION — The CLR Canopy light was designed as an easy to install, economical, and long lasting canopy light. The compact size and wide array of available wattages allows this fixture to fit into a multitude of mounting applications. The round refractor provides an evenly distributed light pattern for exceptional coverage.

CONSTRUCTION — The upper housing is made from die cast aluminum with a powder coat paint finish. It is fully gasketed to a vandal resistant patterned clear polycarbonate lens. ETL listed.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request.


OPTICAL SYSTEM — Multi-patterned, vandal resistant patterned clear polycarbonate lens. Impact resistant and UV stabilized to prevent yellowing. Segmented specular reflector provides 360° illumination.

ELECTRICAL SYSTEM — Available in 70W thru 175W standard metal halide, pulse-start metal halide, and high pressure sodium. Comes standard with a 4KV pulse rated mogul base socket. Each 60HZ CWA multi-tap¹ or 480V ballast is pre-wired and installed for convenience.

MOUNTING — Housing is equipped with four side conduit entries and one top conduit entry. A mounting plate is provided for direct mounting to a standard 4" junction box.



Round Canopy CLR SERIES



Series	Housing Height	Diameter
CLR	11.38"	Ø14.00"

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **CLR5A1-BZ**

CLR		-			
Series	Wattage/Source	Voltage		Finish	
CLR	2A 70W PS Metal Halide 2B 70W High Pressure Sodium 3A 100W PS Metal Halide 3B 100W High Pressure Sodium 4A 150W PS Metal Halide 4B 150W High Pressure Sodium 5A 175W Metal Halide 12A Dual 42W Fluorescent 120V ² 13A Quad 32W Fluorescent 120V ²	1 Multi-Tap ¹ 2 480V		BK Black BZ Bronze GR OD Green USG US Green WH White SP Special ³	

NOTES

- 1 Multi-Tap is 120/208/240/277V wired 277V.
- 2 42W Fluorescent model is only available in 120V. Order using the "1" voltage designation.
- 3 Custom RAL color matching is available. Contact your Techlight sales representative for additional information.