

FEATURES & SPECIFICATIONS

APPLICATION — The CLW Canopy light was designed as an easy to install, economical, and long lasting canopy light. The compact size and range of higher wattages available allows this fixture to fit into a multitude of mounting applications for mid-level height requirements.

CONSTRUCTION — Constructed with a formed and welded aluminum housing with a powdercoat finish. It is fully gasketed to a vandal resistant patterned clear acylic lens assembly to provide weather resistant protection.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request.

OPTICAL SYSTEM — Patterned clear vandal resistant acrylic lens. Segmented high specular aluminum reflector. Type V (360°) photometric pattern.

ELECTRICAL SYSTEM — Available in 175W thru 400W standard and pulse-start metal halide and 150W thru 400W high pressure sodium. Comes standard with a 4KV pulse rated socket. Each 60HZ CWA multi-tap¹ or 480V ballast is pre-wired and installed for convenience.


MOUNTING — Fixture is field drilled according for appropriate mounting application.

Catalog Number	
Project	Туре



Extruded Canopy CLW SERIES





Series	Housing Height	Length & Width
CLW	12.78"	21.50" x 21.50"

Example: CLW5A1-BZ

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

350W PS Metal Halide

CLW Wattage/Source Series Voltage **Pulse-Start** Finish **CLW** 250W Metal Halide A Multi-Tap1 PS Pulse-Start BK Black 400W Metal Halide В 480V BZ 2 Bronze 3 175W Metal Halide GR **US Green** 250W High Pressure Sodium WH White 400W High Pressure Sodium SP Special² 150W High Pressure Sodium 6 7 320W PS Metal Halide

NOTES

- 1 Multi-Tap is 120/208/240/277V wired 277V.
- Custom RAL color matching is available. Contact your Techlight sale representative for additional information.