



Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

FEATURES — UL listed standard for wet locations (0°- 50°C/32°F-122° F). CW option UL listed for wet locations (-20°- 50°C/-4°- 122°F). Meets UL924 NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. Self Diagnostic and Cold Weather features provided standard.

CONSTRUCTION — Decorative, low-profile, architectural design. Die-cast aluminum housing. Durable powder coat finishes in white, black and dark bronze. Sealed and gasketed.

ELECTRICAL SYSTEM — Dual 120V/277V. Charge rate/power “ON” LED indicator light and push to test switch for mandated code compliance testing. Long-life, maintenance-free, rechargeable NiCd battery. Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.


MOUNTING — Surface mount via easy connect back plate that fits most standard size junction boxes. Conduit mount via rigid conduit entry provision on top of the unit.

ILLUMINATION — Long lasting, efficient ultra-bright white LED. Mirror-bright reflector and prismatic polycarbonate refractor.

WARRANTY — Five Year Warranty on all electronics and housing.



Designer Emergency Light DEL SERIES



Series	Housing Height	Length & Width
DEL	10.50"	6.13" x 3.63"

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

DEL		SDCW	
Series	Housing Color	Standard Features	
DEL	BR Brown W White B Black	SD Self Diagnostic	CW Cold Weather

Example: **DELBRSDCW**