



Catalog Number	
Project	Type

Features & Specifications

Application

This fixture is an excellent choice for commercial industrial and retail applications such as storage/utility areas, shops, task and general area lighting.

Features

Optimized for T8 or T5 lamp performance. Premium housing crimped along sides for extra rigidity and straight alignment. Features pressure lock lamp holders. Accepts optional plug-in wiring feature for continuous row installation. Alignment couplers furnished for continuous row installation. Can be surface or pendant mounted, individual or in rows. Numerous KO's for easy installation.

Construction

Fixture housing, lamp holder brackets, end sections and channel over constructed of heavy gauge die-formed steel. Crimped along sides for extra rigidity and straight alignment.

Electrical System

ETL listed. Suitable for damp locations. Damp location emergency pack must be specified separately. Ballasts are solid-state electronic. Ballasts and lamp holders are replaceable without removing from ceiling. Discrete voltage must be specified for emergency pack options when wired with flex.

Finish


All reflective surfaces are finished with a high reflectance, lighting fixture white polyester powder.

NS SERIES NARROW STRIP





DIMENSIONS

Asymmetrical Reflector



Symmetrical Reflector



Please contact your Horizon Sales Representative for more information.

All dimensions subject to change without notice.

Ordering Nomenclature

Ex: (Narrow Strip, 2, F32T8, 4', Multi-Volt =NS232D)

--	--	--	--	--	--	--

SERIES	NUMBER OF LAMPS	WATTAGE	REFLECTOR	VOLTAGE	BALLAST FACTOR	OPTIONS
NS NSA (Aluminum)	1 2 (Per cross section)	14 - 14W T5, 22" 17 - 17W T8, 24" 21 - 21W, T5, 34" 24 - 24W T5HO, 22" 25 - 25W, T8, 36" 28T5 - 28W T5, 46" 28T8 - 28W T8, 48" 32 - 32W T8, 48" 39 - 39W, T5HO, 34" 48HO - 60W 800mA, 48" 54 - 54W T5HO, 46" 59 - 59W T8, 96" 86 - 86W T8HO, 96"	BLANK - None SS - Solid Symmetrical US - Uplight Symmetrical SA - Solid Asymmetrical UA - Uplight Asymmetrical	D - Multi-Volt 1 - 120V 2 - 277V 3 - 347V 4 - 480V *Multi-Volt is 120/277V	BLANK - Normal H - High L - Low	10RS - ≤10% THD, Rapid Start P - Program Start 20 - ≤20% THD EB5 - 500 Lumen T8 Emergency Ballast EB7 - 700 Lumen T8 Emergency Ballast EB14 - 1400 Lumen T8 Emergency Ballast EB30 - 3000 Lumen T8 Emergency Ballast EB5T5 - 500 Lumen T5 Emergency Ballast EB7T5 - 700 Lumen T5 Emergency Ballast EB14T5 - 1400 Lumen T5 Emergency Ballast FBF - Fast-Blow Fuse SBF - Slow-Blow Fuse AC63 - 6', 3/8" dia., Armored Flex Cable SJ6 - 6', 3/8" dia., 16/3 SJ Cord SJ10 - 10', 3/8" dia., 16/3 SJ Cord SJ15 - 15', 3/8" dia., 16/3 SJ Cord PWO - Palletized without Cartons CD - Continuous Dimming (T8) SD - Step Dimming (T8) CD5 - Continuous Dimming (T5) SD5 - Step Dimming (T5) WOC - 120/347 Volt Sensor WOC1 - 480 Volt Sensor C1 - 6' Cord w/120V Nema Plug 16/3 15A C2 - 6' Cord w/277V Nema Plug 16/3 15A C3 - 10' Cord w/277V Nema Plug 16/3 20A C4 - 6' Cord w/480V Nema Plug 16/3 20A WH34 - Wiring Harness 3-Wire 4-Foot WH44 - Wiring Harness 4-Wire 4-Foot
WH54 - Wiring Harness 5-Wire 4-Foot WH38 - Wiring Harness 3-Wire 8-Foot WH48 - Wiring Harness 4-Wire 8-Foot WH58 - Wiring Harness 5-Wire 8-Foot AR2 - 2' Assymetrical Reflector AR3 - 3' Assymetrical Reflector AR4 - 4' Assymetrical Reflector 10JC - (3)S Hooks and 10' Jack Chain Set		THE - Tong Hanger, End Mount (2) THS - Tong Hanger, Side Mount (2) G10 - 10' Aircraft Cable w/ 12" Arms (2) G15 - 15' Aircraft Cable w/ 12" Arms (2) G20 - 20' Aircraft Cable w/ 12" Arms (2) NSWG2 - 2' Wire Guard For Strip NSWG3 - 3' Wire Guard For Strip NSWG4 - 4' Wire Guard For Strip				

Energy Saving Tip!
Our Occupancy Sensor
option instantly turns
lights on and off