



| | |
|----------------|------|
| Catalog Number | |
| Project | Type |

FEATURES & SPECIFICATIONS

FEATURES — Fully gasketed, corrosion-resistant housing. Energy-efficient LED technology. EZ snap-out chevron direction indicators. UL listed for wet locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

CONSTRUCTION — Corrosion-resistant, polycarbonate UV-stabilized housing. Removable KO directional indicators. Single face only. Polycarbonate face plate.

ELECTRICAL SYSTEM — Dual 120V/277V voltage. Charge rate/power “ON” LED indicator light and push-to-test switch for mandated code compliance testing. LVD (low voltage disconnect) prevents battery from deep discharge. Long-life, maintenance-free, rechargeable NiCd battery (B Model). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING — Knockouts for back mounting.


ILLUMINATION — Standard with two 5.4 watt tungsten fully adjustable, glare-free incandescent emergency lighting heads. High-performance smooth thermoplastic reflector and plastic lens for optimal light distribution. Ultra-bright, energy efficient, long-life Red or Green LED (exit sign illumination). 6” EXIT letters.

WARRANTY — Five Year Warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.



Wet Location Exit/Emergency Combo

CWLE SERIES



| Series | Housing Height | Length & Width |
|-------------|----------------|----------------|
| CWLE | 18.25" | 11.75" x 3.75" |

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

| CWLE | | | |
|-------------|--------------------------------|--------------------------|---------------------------|
| Series | Letter Color | Battery | Options |
| CWLE | R Red G Green | B Battery Back-Up | HT Internal Heater |

Example: **CWLERB**