



Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

FEATURES — Compact, low-profile design in neutral finish. UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

CONSTRUCTION — Injection-molded, engineering-grade, V-0 flame retardant, high-impact, thermoplastic in white or black finish.

MOUNTING — Universal mounting plate.

ILLUMINATION — One or two fully adjustable 6V-5.4W and 9W, or 12V-7.2W and 12W glare-free lighting heads.

WARRANTY — Five Year Warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.



**Remote Head Emergency Light
RH SERIES**



ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **RH16V9WW**

RH									
Series	Number of Heads	Voltage		Wattage		Finish			
RH	1 Single 2 Dual	6V 6 Volt 12V 12 Volt		<u>6V Only</u> 5.4W 9W <u>12V Only</u> 7.2W 12W		W White B Black			

- NOTES
- 1 18W and 27W units available in 6V only.
 - 2 50W unit available in 12V only.
 - 3 Remote Capable option available on 50W unit only.