



Catalog Number	
Project	Type

# WL SERIES

## Large LED Burial Light



SERIES	HOUSING HEIGHT	DIAMETER
<b>WLAR</b>	18"	10"

**LISTINGS** — ETL listed for wet locations. Meets US and Canadian safety standards.

### FEATURES & SPECIFICATIONS

**APPLICATION** — The landscape burial light are the most versatile fixtures on the market. Various beam spreads and wattages allow for a customized finish to any property. The high end residential grade system was designed for 120V operation residential applications.

**CONSTRUCTION** — The die cast aluminum, brass, or zinc housings suspend from the covering grill by two steel spring clips. The grill is secured to the well sleeve with two self-tapping screws.

**OPTICAL SYSTEM** — A high-impact tempered glass lens is sealed to the housing using silicone for a watertight seal. The aluminum or brass safety grill rotates 360° for glare control.

**ELECTRICAL SYSTEM** — Fixture can be used with PAR 38 or R40 LED lamps. Each fixture is pre-wired with either 15' or 30' of 16/3 cable and is internally grounded.

**MOUNTING** — Fixtures are designed to be in-ground well lights and should be installed according to the installation instructions made available by Techlight. Proper drainage and substrate must be provided for water to flow freely through the well sleeve.

### ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

SERIES	CORD	SLEEVE	GRILL
<b>WLAR4</b> = Aluminum body <b>WLBR4</b> = Brass body <b>WLZR4</b> = Zinc body	<b>15-1</b> = 15' Cord <b>30-1</b> = 30' Cord	<b>1</b> = Burial Light Sleeve	<b>1</b> = Aluminum Grill <b>2</b> = Brass Grill

**EXAMPLE:**

**WLAR4-30-1-1-2**

### ACCESSORIES

(Order as separate line items)

**TLHB800RCH**

Digital Timer



### LAMPS

(Order as separate line items)

**LUVPAR3820WXXK<sup>1,2</sup>** LED 20W PAR38

### NOTES

- 1 = Recommend minimum one surge protection device for each circuit. See [FSPENCA277VM Series](#) specification sheet for details.
- 2 = XX could be 27 = 2700K, 30 = 3000K, 40 = 4000K, 65 = 6500K or GR = Green Lens. See [LUV Series](#) specification sheet for details.

### AVAILABLE FIXTURE DIMENSIONS

Dimensions shown are for fixture bodies only. Mounting options must be ordered separately.

